


Paint mixer RM 5001



Paint mixer RM 5001 – Free-standing model, version AIR



Paint mixer as basic version RM 5001/00, but suitable for use in  sectors, i.e. areas where there is a risk of explosion.

All drives and the clamping fixture are operated by compressed air.

Ref RM 5001 / Air

- Timer: max. 5 min.
- Fixed speed: ca. 640 rpm
- Paint mixer, standard version, for batch sizes from 0.5 l to 10 litres (max. 30 kg)
- The mixing chamber is loaded by way of a specimen plate through a swing door with safety locking feature.

o The paint lot is clamped by air-operated motor.

- Mixing times are pre-selected using a continuously variable timer (time pre-selection: max. 5 min.)
- Operating panel located above the test chamber.



manually by hand crank

Technical data

- Dimensions : H x W x D 1210 x 650 x 650 mm
- Weight : 225 kg
- Paint finish : **Powder coating**, RAL 3000
- Compressed air: : 6 bar - 110 qm/h / 27 qm/h
- Pressure gauge : : Compressed air 6 bar, filtered air 3.2 bar
- Motor drive : : 1,400 / 640 rpm (50 mm stroke)
- Noise emission Empty without load 68 dbA
- Motor: 0.75 kW – Clamping motor 0.2 kW (air)



electronic clamping

Accessories: Servicing unit for compressed air

- Oiler
- Pressure reducer
- Condensate trap



Plug-in coupling and pressure gauge